

OnSite PRO Inc.

FLOODSTOP™

Stop Flood Damage Before It Really Starts!

FloodStop FS3/4H-90 is a point of use, leak detection and automatic water shut-off system designed for residential and commercial dwellings. The FS3/4H-90 uses two Motorized Ball Valves to automatically shut off the water supply whenever your washing machine leaks, overflows, or a hose bursts!

Statewide Supply Inc
7352 Darlin Ct Unit 1
Dane, WI 53529

(800) 553-5573 Phone
(608) 850-5558 Fax
www.statewidesupply.com



Install in Minutes!

Kit includes everything you need to protect your property:

- 3/4" Motorized Ball Valves installed on both hot and cold water inlets.
- Water sensor is placed on the floor.
- Control Unit is mounted with screws or Velcro (included).
- Optional Power Sources: AC & (4) AA Batteries, or Batteries alone!

Technical Specifications:

- UL listed class 2 wall adaptor, 115AC/9VDC
- Signal Output: 1 Normally Open, 24 Volt / 2 amp rated
- Motorized Ball Valves (2): CNC machined with 90 degree downward outlet.
- Motors operate at 6VDC. AB1953, UPC, CUPC, NSF61 cert.
- Rated 0-180 PSI. Max 250 PSI. Solid brass.
- Rated 32-212 degrees F
- Sensor: 1.25 X 7.5 inch, double sided. Additional sensors may be added in series.
- Alarm: Beeping with Mute button.

Washing Machines FS3/4H-90 3/4" Hose Fittings



FloodStop Product Lineup:

FS3/4H-90 Washing Machine (Hose Fittings)
FS3/4H Washing Machine (Hose Fittings)
FS3/4NPT Water Heater 3/4" (MIP X FIP)
FS3/4C Water Heater (3/4" Compression)
FS100NPT Water Heater (1.00" (MIP X FIP)
FS125NPT Water Heater (1.25" (MIP X FIP)
FS1/2NPT Water Heater 1/2" (MIP X FIP)
FS3/8C Dishwasher, Toilet (3/8" Compression)
FS3/8CD Sink (3/8" Compression)
FS1/4C Ice Maker (1/4" Compression)